



Quality is in our nature

Transmission oils - Fully Synthetic

# Eurol MTF 75W-85 FE GL-5

## Full synthetic gear oil with fuel-saving properties

### Description

Eurol MTF 75W-85 FE GL-5 is a fully synthetic fuel-saving transmission oil, which can be used in manual transmissions and final drives, for which GL-5 is required.

Eurol MTF 75W-85 FE GL-5 ensures adequate lubrication at both very low, as very high temperatures and protects against corrosion, wear, thickening and deposits.

Eurol MTF 75W-85 FE GL-5 is very well compatible with synchromesh and ensures very smooth shifting even at low temperatures.

Eurol MTF 75W-85 FE GL-5 is compatible with most elastomers and seal materials and does not foam under extreme loads.

Eurol MTF 75W-85 FE GL-5 has an excellent high load carrying capacity for an excellent absorption of sudden peak loads. The viscosity decrease due to heavy loads is only slightly, which will extend oil drain intervals (and in some cases lifetime filling) and ensures proper viscosity.

Eurol MTF 75W-85 FE GL-5 contains special friction modifiers, which ensure sustainable fuel saving and less heat development. In addition, this oil is ideal for limited slip differentials.

### Performance Level

Meets requirements of VW G 055 190 A2

API GL-5

MB 235.7

ZF TE-ML 18

#### Performance level

Alfa Romeo

BMW

Fiat

LANCIA

VW G 052 145 A1

VW G 052 190 A2

### Physical properties

Colour	Amber	
Density at 20°C	0.87 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	81.5 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12.1 cSt	ASTM D 445
Flash point	190 °C	ASTM D 93
Pour point	-51 °C	ASTM D 97

Available in 1L - 20L - 60L

E110081

Version 1.0, 04-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com