



Quality is in our nature

Passenger car engine oils - Fully Synthetic

Eurol Syntence 5W-30

Fully synthetic long-life motor oil VW 504.00/507.00; MB 229.51

Description

Eurol Syntence 5W-30 is a fully synthetic motor oil for use in gasoline, LPG and diesel engines of passenger cars and light duty commercial vehicles, equipped with soot filters (to meet Euro-4 exhaust emission regulations). This product has been especially developed for passenger cars and light duty commercial vehicles of the VAG group (Volkswagen, Audi, Seat and Skoda) and is suitable for very long drain intervals (up to 30.000 km for gasoline and 50.000 km for diesel engines).

Further tests proved that the product meets the specification MB 229.51; this oil is therefore not only universally applicable for Volkswagen, but also for Mercedes. Meets ACEA C2 requirements concerning motor protection.

Eurol Syntence 5W-30 provides an extremely quick and stable lubricant film at the cold start and maintains this film at high temperatures, while at the same time, friction is reduced to a minimum.

Eurol Syntence 5W-30 has been especially developed to meet VW specifications 504.00 and 507.00, but is also suitable for cars where formerly VW specifications like 503.00, 506.00, 506.01, 505.01, 502.00, 500.00, 501.01 and 505.00 are prescribed.

Specifications

Approved

VW 504.00

VW 507.00

MB-Approval 229.51

BMW Longlife-04

Performance level

API SN

ACEA C3

Porsche C30

Recommended for use

Fiat 9.55535-S3

Physical properties

Colour	Brown	
Density at 20°C	0.85 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	71.2 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12.3 cSt	ASTM D 445
Viscosity Index	172	ASTM D 2270
Viscosity, dynamic (CCS) at -30°C	5590 cP	ASTM D 2602
Base number	6.7 mg KOH/g	ASTM D 2896
Sulphated ash	0.67 wt%	ASTM D 874
Flash point	207 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

Available in 1L - 4L - 5L - 20L - 60L - 200L - 210L - IBC - BULK

E100062

Version 2.0, 06-12-2018

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com