



Quality is in our nature

Passenger car engine oils - mid SAPS

# Eurol Evolence 5W-20

## Fully synthetic long-life motor oil based on mid SAPS technology

### Description

Eurol Evolence comprises a fully synthetic range of motor oils for gasoline engines in passenger cars. This oil can be used in cars equipped with catalytic converters, turbo charged engines, and direct injection systems, where API SN(-RC) (as well as SJ, SL and SM) or ILSAC GF-5 (as well as GF-2,-3 and-4) is prescribed.

Eurol Evolence, manufactured with Eurol's OPT additives, offers an extremely high protection, also for turbochargers, over prolonged drain intervals.

Eurol Evolence controls high temperature oxidation and deposits and prevents sludge and varnish formation from surfaces and meet the highest 2010 U.S. standards for engine wear protection.

Eurol Evolence offers improved fuel economy and fuel economy retention resulting in lower emissions. Furthermore it is compatible with gasoline fuels containing up to 85% ethanol (E85). The Eurol Evolence is suitable for modern hybrid cars for car brands like

Toyota, Honda and Lexus.

Eurol Evolence can be used where GM 6094M, Chrysler MS 6395 and Ford WSS-M2C-945A or 946A is prescribed, whereas Eurol Evolence 0W-20, 0W-30, 5W-20 and 5W-30 also fulfills the requirements of GM dexos1.

For certain severe applications, such as stop-and-go or heavy loads, drain intervals should be reduced significantly, as being mentioned in some manuals.

If the quality needed for a specific vehicle is not mentioned under "performance level", the applicability of this oil should be checked, in the manufacturers advice, or in the Eurol Product Advisor on [www.eurol.com](http://www.eurol.com)

### Specifications

#### Performance level

API SN-RC  
ILSAC GF-5

#### Recommended for use

Ford WSS-M2C945-A  
Ford WSS-M2C930-A  
Fiat 9.55535-CR1  
Chrysler MS 6395  
GM 6048-M

### Physical properties

Colour	Amber	
Density at 20°C	0.849 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	45.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	8.7 cSt	ASTM D 445
Viscosity Index	172	ASTM D 2270
Viscosity, dynamic (CCS)	3431 cP	ASTM D 2602
Base number	8.5 mg KOH/g	ASTM D 2896
Flash point	209 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

Available in 1L - 5L - 60L - 200L - 210L

E100130  
Version 1.0, 03-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, [info@eurol.com](mailto:info@eurol.com), [www.eurol.com](http://www.eurol.com)