



Quality is in our nature

Heavy duty diesel engine oils - low SAPS

Eurol Marathol 10W-40

UHPD motor oil, based on low SAPS technology

Description

Eurol Marathol 10W-40 is an ultra high performance motor oil for commercial vehicles based on the so called 'low SAPS' technology. This means that sulphur, phosphorus and sulphated ash concentrations are reduced radically, to protect the exhaust gas after treatment systems.

Especially Mercedes (228.51) and MAN (M3477) have set up special standards for the oil to meet Euro-4 and Euro-5 emission regulations, including reduced sulphur, phosphorus and sulphated ash concentrations. For this reason, ACEA launched the E6 specification at the end of 2004.

Eurol Marathol 10W-40 has fuel economy properties and because of the special additive technology, both the oil and the engine are kept clean in an unprecedentedly way. In Euro-4, 5 and Euro-6 engines the harmful exhaust gas emission is reduced.

Eurol Marathol 10W-40 is suitable for extended drain intervals, if allowed by the OEM and depending on working conditions and filtration methods, so it reduces maintenance cost.

Eurol Marathol 10W-40 can also be applied in older trucks with Euro-3 engines, where ACEA E4, Mercedes 228.5 and MAN 3277 are prescribed, as well Renault RXD and DAF HP-2.

Specifications

<u>Approved</u>	ACEA E9
MB-Approval 228.51	MB 226.9
MAN M 3477	Renault RXD
MAN M 3271-1	CES 20076
Volvo VDS-3	CES 20077
Renault RD-2	MTU type 3.1
Mack EO-N	Renault RGD
<u>Performance level</u>	DAF
API CI-4	JASO DH-2
ACEA E6	Deutz DQC IV-10-LA
ACEA E7	Deutz DQC TTCD

Physical properties

Colour	Brown	
Density at 20°C	0.859 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	95.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.4 cSt	ASTM D 445
Viscosity Index	157	ASTM D 2270
Viscosity, dynamic (CCS)	5374 cP	ASTM D 2602
Base number	10.1 mg KOH/g	ASTM D 2896
Sulphated ash	0.99 wt%	ASTM D 874
Flash point	210 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

Available in 5L - 20L - 60L - 200L - 210L - IBC - BULK

E100119
Version 1.0, 19-12-2018

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com