



Quality is in our nature

Heavy duty diesel engine oils - Mineral

Eurol Bediga 20W-50

Mineral motor oil for mixed fleet

Description

Eurol Bediga 20W-50 is an engine oil providing an optimum lubrication for older passenger cars and light loaded commercial vehicles equipped with gasoline, LPG and diesel engines.

Eurol Bediga 20W-50 is suitable for turbo charged engines, multi-valve technology and engines with catalytic converters.

Eurol Bediga 20W-50 offers excellent wear protection to all engine parts. These parts will also be protected against rust and corrosion. Special deterging additives keep rust particles and soot in dispersion. Eurol Bediga 20W-50 also contains special additives to prevent from oil thickening caused by oxidation at high temperatures.

Due to the use of shear stable viscosity index improves the viscosity will stay in grade, so that also during long drain interval terms, Euro Bediga 20W-50 will continue to provide a strong lubricant film between the moving parts of the engine.

Specifications

Performance level

API SG/CF-4

Recommended for use

MIL-L-46152

MIL-L-2104D

Physical properties

Colour	Brown	
Density at 20°C	0.877 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	161 cSt	ASTM D 445
Viscosity, kinematic at 100°C	18.6 cSt	ASTM D 445
Viscosity Index	129	ASTM D 2270
Viscosity, dynamic (CCS)	6022 cP	ASTM D 2602
Base number	7.6 mg KOH/g	ASTM D 2896
Sulphated ash	1.07 wt%	ASTM D 874
Flash point	219 °C	ASTM D 93
Pour point	-33 °C	ASTM D 97

Available in 1L - 4Q - 4L - 5L - 10L - 20L - 25L - 30L - 60L - 200L - 210L - IBC - BULK

E100045

Version 3.0, 06-12-2017

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com