



Quality is in our nature

Technical fluids - Powersteering

Eurol Powersteering fluid C

Fully synthetic hydraulic oil for levelling and power steering systems

Description

Eurol Powersteering Fluid C is a full synthetic hydraulic fluid, especially developed for hydraulic systems like levelling systems and power steering systems in tractors, passenger cars and commercial vehicles.

Eurol Powersteering Fluid C has a very high viscosity index and a very low pour point. Due to these features, the viscosity will hardly change under varying temperatures.

Eurol Powersteering Fluid C protects the system against oxidation. Because of the high boiling point and the water resistance, the product can be applied for a long lasting and safe use when this type of fluid is prescribed.

Specifications

<u>Performance level</u>	GM/Opel 19 40 715/766
Porsche 000 043 206 56	Porsche
DIN 51524/3 (HVLP)	000.043.203.33/000.043.20
VW TL 52 146 (G002	6.56
000/G004 000)	Volvo 1161529/30741424
Volvo 30741424	ZF TE-ML 02K
ISO 7308	MB 345.0
Hyundai 00232-19017	MAN M 3289
GM/Opel B 040 2012	
<u>Recommended for use</u>	
Ford WSS-M2C204-A/A1	

Physical properties

Colour	Green	
Density at 20°C	0.84 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	19 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6 cSt	ASTM D 445
Viscosity Index	303	ASTM D 2270
Flash point	156 °C	ASTM D 93
Pour point	-58 °C	ASTM D 97

Available in 1L - 20L - 60L - 200L - 210L

E113675
Version 1.0, 04-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com