



Quality is in our nature

Technical fluids

Eurol MHF 4400

Fullsynthetic oil for specific Mercedes levelling systems

Description

Eurol MHF 4400 is a fully synthetic hydraulic fluid, specially formulated for levelling systems of certain Mercedes passenger cars. (In particular the models 203.2 and 210 with tandempumps with shared oil reservoir for steering and level control.)

conventional hydraulic fluids, mixing is discouraged in order to benefit of the unique properties of Eurol MHF 4400.

Eurol MHF 4400 ensures a superiour wear protection as well as excellent fluidity, even at very low temperatures. Eurol MHF 4400 also shows dedicated friction characteristics and offers adequate protection against corrosion and alteration.

Eurol MHF 4400 is formulated for applications (levelling systems and power steering) where the MB 344.0 specification is prescribed.

Eurol MHF 4400 ensures a good working hydraulic system under all circumstances in particular because of the excellent damping characteristics.

Although Eurol MHF 4400 is miscible with most of the

Specifications

Performance level

MB 344.0

Physical properties

Colour	Brown	
Density at 20°C	0.855 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	30.6 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6.2 cSt	ASTM D 445
Flash point	200 °C	ASTM D 93
Pour point	-68 °C	ASTM D 97

Available in 1L - 20L - 60L

E108676
Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com