



Quality is in our nature

Transmission oils - Mineral

# Eurol Eurolube SAE 80W GL1

Mineral transmission oil for light duty gears with straight- and bevel teeth

## Description

Eurolube is blended with solvent refined paraffinic base stocks and anti-wear additives. The product is recommended for light duty gearboxes with straight or bevel teeth.

Eurolube has a high viscosity index and a low pour point which guarantees a constant safe operating condition, both at low starting temperatures as well as at high full load temperatures.

Seals are not affected by Eurolube. The product has an excellent thermal and oxidation stability, ensuring a long durability. Parts are protected from rust and corrosion.

## Specifications

Recommended for use

API GL-1

## Physical properties

Colour	Amber	
Density at 20°C	0.867 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	68.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	9 cSt	ASTM D 445
Viscosity Index	107	ASTM D 2270
Flash point	220 °C	ASTM D 93
Pour point	-27 °C	ASTM D 97

Available in 250ML - 500ML - 1L - 20L - 25L - 60L - IBC - BULK

E110500

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com