



Quality is in our nature

Technical fluids

# Eurol MHF 4300

## Mineral oil for specific Mercedes levelling systems

### Description

Eurol MHF 4300 is a mineral hydraulic fluid, specially developed for Level control system, hydropneumatic suspension, hydraulic system from ASD, 4MATIC and soft top (convertible top) in certain Mercedes-Benz passenger cars.

conventional hydraulic fluids, mixing is discouraged in order to benefit of the unique properties of Eurol MHF 4300.

Eurol MHF 4300 ensures a superiour wear protection as well as excellent fluidity, even at very low temperatures. Eurol MHF 4300 also shows dedicated friction characteristics and offers adequate protection against corrosion and alteration.

Eurol MHF 4300 is formulated for applications (levelling systems, shock absorbers and power steering) where the MB 343.0 specification is prescribed.

Eurol MHF 4300 ensures a good working hydraulic system under all circumstances in particular because of the excellent damping characteristics.

Although Eurol MHF 4300 is miscible with most of the

### Specifications

#### Performance level

MB 343.0

#### Recommended for use

DIN 51524/3 (HVLP)

ISO 7308

### Physical properties

Colour	Yellow	
Density at 20°C	0.865 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	20 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6.2 cSt	ASTM D 445
Viscosity Index	280	ASTM D 2270
Flash point	100 °C	ASTM D 93
Pour point	-51 °C	ASTM D 97

Available in 1L - 20L - 60L

E108675  
Version 1.1, 16-04-2018

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com